

HIGH MILEAGE 10W-30 / 10W-40

A SUPER PREMIUM GASOLINE ENGINE OIL – API SM

A PRODUCT OF ROADVIEW® ENERGY

Product Description

SAE 15W-50 is designed to meet the warranty requirements of most manufacturers of Heavy Duty Diesel engines operating on high sulfur fuels. The high alkaline reserve (TBN) effectively protects bearings and other engine surfaces from the corrosive effect of acids formed by the combustion of high sulfur fuels. Extended drain service where ever recommended by original equipment manufacturers (OEMs).

This motor oil is a blend of highly refined base oils and specially selected additives designed to provide excellent performance in all recommended applications. Contains effective detergent-dispersant to keep sludge and varnish deposits to a minimum. Additionally fortified with oxidation-corrosion inhibitors, high temperature anti-wear additives and foam inhibitors, to protect vital engine parts from scuffing and protect bearings from corrosion.

Advantages

- High Mileage 10W30 & 10W40 exceeds API Service Classification SM and is recommended for domestic and foreign high performance engines. It is recommended for small, high RPM engines including those that are turbocharged.
- Recommended for passenger cars, light duty pickups, motorcycles and other gasoline engines in mobile and stationary service.
- Exceeds requirements of OEM requirements like Chrysler, Ford, GM, Toyota, Honda etc.

Features

- Grades 10W30 /10W40 meets and exceeds U.S. car maker warranty requirements for API SM.
- Minimum ash deposits on Spark Plugs, Combustion chamber and valve surfaces.
- High mileage permits extending drain interval to maximum allowed by engine manufacturer
- Effective detergent-dispersants keeps engine parts clean.
- High oxidation stability - Protects engine against sludge and varnish deposits.
- High TBN/alkaline reserve effectively neutralizes corrosive acids formed by combustion to protect critical turbo bearings and other vital engine surfaces.

Typical Test Data

TEST, GRADE	ASTM	10W-30	10W-40
Gravity, °API	D-287	31.5	32.0
Flash Point, °C	D-92	420	430
Pour Point, °C	D-97	-30	-25
Viscosity:			
cSt @ 100 °C	D-445	11.1	14.1
CCS @ - 25 °C	D-5293	6,000	7,000
Viscosity Index	D-2270	145	150
Appearance	Visual	Bright & Clear	Bright & Clear
Color	D-1500	2.5	2.5
Zinc. WT. %		0.085	0.085
TBN	D-2896	6.5	6.5

* Minor variations in product typical test data are to be expected in normal manufacturing.

TECHNICAL PRODUCT INFORMATION