

# ROUND TRIP 5W-30 ILSAC GF-5, API SN

A PREMIUM HIGH PERFORMANCE ECO FRIENDLY GASOLINE ENGINE OIL – ILSAC GF-5, API SN

A PRODUCT OF ROADVIEW® ENERGY

## Product Description

**ROUND TRIP 5W-30, ILSAC GF-5, API SN** is formulated to be an environmentally responsible engine lubricant. It uses the highest quality of re-refined Base oils and selected additives, designed to give excellent performance in all recommended applications.

This engine oil contains an effective detergent-dispersant which keeps the modern engines highly clean.

It is formulated based on "ECO" friendly base oils to help Energy Conservation. The product is fully fortified with oxidation-corrosion inhibitors, extreme pressure additives, foam inhibitors to protect vital engine parts from scuffing and to protect bearings from corrosion.

This product contains greater than 70 % of "re-refined" base oil.

## Advantages

- Roundtrip exceeds ILSAC & API Service Classification for GF-5 and SN and is recommended for domestic and foreign high performance engines. It is recommended for small, high RPM engines including those that are turbo-charged.
- Recommended for passenger cars, light duty pickups, motorcycles and other gasoline engines in mobile and Stationary service.

## Features

- SAE 5W-30 meets and exceeds U.S. car maker warranty requirements.
- Meets and exceeds today's demanding energy conservation requirements.
- Effectively neutralizes corrosive acids to protect bearings and other vital engine surfaces.
- Highly oxidation stable - protects engine from oil thickening, high temperature sludge and varnish deposits.
- Shear stable viscosity index improver-protects against viscosity breakdown in severe service.
- Effective detergent-dispersants keeps engine parts clean.
- High TBN / alkaline reserve effectively neutralizes corrosive acids formed by combustion to protect critical turbo charger bearings and other vital engine surfaces.
- Anti-wear agents effectively protect cam lobes and other highly loaded parts from wear.

## Typical Test Data

TEST, GRADE	ASTM	5W-30
Gravity, °API	D-287	33.5
Flash Point, °C	D-92	220
Pour Point, °C	D-97	-39
Viscosity:		
cSt @ 100 °C	D-445	10.7
CCS @ - 25 °C	D-5293	5,300
Viscosity Index	D-2270	>140
Appearance	Visual	Bright & Clear
Color	D-1500	3.0
Calcium. WT. %		0.18
Zinc. WT. %		0.08
TBN	D-2896	7.8

\* Minor variations in product typical test data are to be expected in normal manufacturing.

## TECHNICAL PRODUCT INFORMATION