

XLD SUPREME PREMIUM SAE 15W-40 MOTOR OIL

A LONG DRAIN 10 TBN DIESEL ENGINE OIL API SERVICE CI-4/SL



A PRODUCT OF ROADVIEW® ENERGY

Product Description

XPD Super Premium Motor Oil is a super premium heavy duty diesel engine oil designed to meet the warranty requirements of most manufacturers of diesel engines equipped with EGR valves and was specifically developed for diesel engines operating on high sulfur fuels. The high alkaline reserve (TBN) effectively protects bearings and other engine surfaces from the corrosive effect of acids formed by the combustion of high sulfur fuels. Recommended for extended drain service when suggested by original equipment manufacturer.

This motor oil is a blend of highly refined base oils and specially selected additives designed to provide excellent performance in all recommended applications. Contains effective detergent-dispersant to keep sludge and varnish deposits to a minimum. Additionally fortified with oxidation-corrosion inhibitors, high temperature anti-wear additives and foam inhibitors, to protect vital engine parts from scuffing and protect bearings from corrosion.

Advantages

- Exceeds the service classifications CI-4/SL. These products are recommended for diesel engines using high sulfur fuels.
- Meets Mack EO-N Premium Plus and EO-M Plus requirements.
- Meets and exceeds service requirements for Cummins CES 20076 / 20077, MB 228.3.
- Recommended for all turbo-charged engines where manufacturer specified a CI-4, CH-4, CG-4, CF-4,CF or MIL-L-2104D / MIL-L-2104F level oil.
- Meets requirement of Allison C-4, Volvo VDS requirements
- Meets ACEA E2 and Global DHD-1 requirements.

Features

- High TBN/Alkaline Reserve – Effectively neutralizes corrosive acids to protect bearings and other vital engine surfaces.
- Minimizes ash deposits in combustion chamber and valve surfaces.
- Highly oxidation stable – protects engine against sludge and varnish deposits.
- Effective anti-scuff additive protects cam lobes and other highly loaded parts from wear.
- 10 TBN is extremely useful for all those high sulfur fuels that are available in various regions.
- Designed to meet 2002 emission standards and beyond.

Typical Test Data

TEST, GRADE	ASTM	15W-40
Gravity, ° API	D-287	30.2
Flash Point, °C	D-92	440
Pour Point, °C	D-97	-25
Viscosity:		
cSt @ 100 °C	D-445	14.6
Viscosity Index	D-2270	139
Color	D-1500	3.0
Sulfated Ash, Wt. %		>1.30
Zinc, WT. %	D-4927	0.12
TBN	D-2896	10

* Minor variations in product typical test data are to be expected in normal manufacturing.

TECHNICAL PRODUCT INFORMATION

Product Code: 22127

© 2017 Roadview Energy Investments & Services, LLC. All rights reserved.
Roadview Lubricating Oil Hallmark is trademark owned by Roadview Energy.
All other trademarks are property of their respective owners.
MADE IN U.S.A.